



Product Sheet MASKING TAPE - MTE



MASKING TAPE - MTE

The original crepe paper masking tape

High performance
refinish grade - a
bodyshop essential

Exceptional mechanical performance



80° C temperature
resistance



Natural rubber resin
adhesive



Consistency of thickness



Features and Benefits

Solvent resistant >> Paint will not bleed

Excellent adhesion >> Good mechanical strength

Flexible >> Easy to shape on contours

Easy/clean removal >> Leaves no residue

Consistency of thickness >> Uniform paint edge

Easy roll release >> Easy to apply

80° temp rating >> Low bake refinishing

Substrates

Old paint

Fillers

Primers

Top Coats

Clear Coats

Gel Coat

Wood Coatings

Walls and Dry Walls

Painted Surface

Primed Surface

Composite

Plastic

Applications

Automotive masking

Paint and Decorative masking

Suited for



Automotive Refinishing



Composite Industries

Technical Specifications

Colour	Ivory	Ivory	Ivory	Ivory	Ivory	Ivory	Ivory	Ivory
Width	12 mm	15 mm	18 mm	24 mm	30 mm	36 mm	48 mm	72 mm
Length	50 m	50 m	50 m	50 m	50 m	50 m	50 m	50 m
Backing	Semi-crepe paper	Semi-crepe paper	Semi-crepe paper	Semi-crepe paper	Semi-crepe paper	Semi-crepe paper	Semi-crepe paper	Semi-crepe paper
Adhesive	Natural rubber	Natural rubber	Natural rubber	Natural rubber	Natural rubber	Natural rubber	Natural rubber	Natural rubber
Thickness	0,135mm	0,135mm	0,135mm	0,135mm	0,135mm	0,135mm	0,135mm	0,135mm
Temperature Resistance	80° - 30 min	80° - 30 min	80° - 30 min	80° - 30 min	80° - 30 min	80° - 30 min	80° - 30 min	80° - 30 min
Removal Time Indoor	5 days	5 days	5 days	5 days	5 days	5 days	5 days	5 days
Elongation at Break	9,5%	9,5%	9,5%	9,5%	9,5%	9,5%	9,5%	9,5%
Adhesion to Steel	270 g/cm	270 g/cm	270 g/cm	270 g/cm	270 g/cm	270 g/cm	270 g/cm	270 g/cm
Rolling Ball Test	1 cm	1 cm	1 cm	1 cm	1 cm	1 cm	1 cm	1 cm
Tensile Strength	4,0 kg/cm	4,0 kg/cm	4,0 kg/cm	4,0 kg/cm	4,0 kg/cm	4,0 kg/cm	4,0 kg/cm	4,0 kg/cm
Package Qty.	72	60	48	36	32	24	20	12